



PRODUCTS:

1. OASIS DP STD
2. OASIS DP PUMP

**PERFORMANCE
DATA SHEET**

PERFORMANCE DATA SHEET

MANUFACTURER

Name: ATLAS FILTRI SRL

Address: Via Pierobon 32 - Limena, 35010, PD

Phone Number: +39 049769055

SELLER:

Name: Atlas FILTRI S.r.l.
distributors

PRODUCTS

- OASIS DP STD
- OASIS DP PUMP

SUBSTANCES REDUCTION

The Atlas Filtri models listed above have been tested and certified under AS/NZS 4020 and AS 3497 and relevant NSF Standard listed in Clause 1.2 for reduction of Sediment. The performance of these products has been verified and substantiated as the test data summarized below indicates. These substances may not be in your water.

CLAIM TYPE	TREATMENT TYPE	PLAIN LANGUAGE DESCRIPTION	CONFORMANCE TO NSF STANDARDS AND PROTOCOLS	CATEGORY
N/A	Bacteriostatic	Will stop bacteria increasing but will not remove them	NSF/ANSI 42	I
N/A	Bacteria removal	Will remove or inactivate bacteria	NSF/ANSI 55	II(a)
N/A	Virus removal	Will remove or inactivate viruses	NSF/ANSI 55	II(b)
N/A	Protozoa removal	Will remove or inactivate Cryptosporidium and Giardia	NSF/ANSI 53	II(c)
N/A	Turbidity and particulate removal	Reduce Cloudiness	NSF/ANSI 42	III
Verified	Taste and Odour reduction	Reduces tastes and odour	NSF/ANSI 42	IV
Verified	Chemical contaminant reduction	Decreases certain chemicals	NSF/ANSI 42	V

Substance	NHMRC ADWG or USEPA SDWA MCL	Average Influent Concentration	Maximum Effluent Concentration	Minimum Percent removal	Average Effluent Concentration	Average percent removal
Chlorine	4 mg/l	1.94 mg/l	0.54 mg/l	70.7%	0.28 mg/l	86.2 %

MCL - Maximum Contaminant level

Mg/l - milligrams per litre

Testing conditions:

- Flow rate was controlled at 1 gpm
- pH 7,8 +/- 0,05
- Temperature 21 +/- 3 degrees C

Refer to your owner's guide for more specific product and warranty information and to avoid contamination from improper handling and installation. Performance will vary on local water conditions. The substances reduced by this product are not necessarily in your water.

USE GUIDELINE

- Minimum Operating pressure 50 kPa
- Maximum operating pressure 600 kPa
- Do not Allow exposure to temperature below 4 °C
- Maximum operating temperature 40°C
- Nominal Flow rate:
Min. feed flow
OASIS DP STD 0.13 l/min
OASIS DP PUMP 0.13 l/min

ELECTRICAL REQUIREMENTS

- Power supply: AC 110-240 V; 50/60 Hz
- Diaphragm booster pump
model OASIS DP PUMP: 16 W
- Total consumption
model OASIS DP PUMP: 16 W

- This system has to be installed according to local plumbing codes on the cold water line
- Replacement cartridges

OASIS DP STD cartridge CPP 10 SX - LA 10 SX TS - CB-EC 10
 OASIS DP PUMP cartridge CPP 10 SX - LA 10 SX TS - CB-EC 10

- This system requires regular replacement of the filter cartridge to maintain proper operation. Varying Sediment or organic substances levels may affect replacement frequency.
- Be sure to change the filter cartridge at least every six months; Or whenever you detect a change in taste or odour or decrease in flow.



CAUTION - Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for CYST reduction may be used on disinfected water that may contain filterable CYSTS.

Buyer's Signature

Date

Seller's Signature

Date

.....

.....

.....

.....

We value
what really
matters.
Water



IT'S MADE IN ITALY



ATLAS FILTRI S.r.l. | via Pierobon, 32 | 35010 Limena, Italy
Tel. +39.049.76.90.55 | Fax +39.049.76.99.94 | www.atlasfiltri.com