# TM aleArr

melt-blown polypropylene and ScaleArmor<sup>™</sup> media

Cartridges combining a pre-filter element made from melt-blown polypropylene with ScaleArmor<sup>™</sup> media for anti-scale water conditioning. CPP ScaleArmor<sup>™</sup> cartridges provide fine sediment pre-filtration at 5 micron and anti-scale and anti-corrosion treatment with proven effectiveness that removes with time old calcareous incrustations and offers a corrosion protection for boilers, pipes, pumps and appliances. CPP ScaleArmor<sup>™</sup> cartridges are available in 10" and 20" heights, standard and BIG (4,5" OD)



MAX WORKING TEMPERATURE 45°C (113°F) MIN WORKING TEMPERATURE 4°C (39,2°F)

## COLDWATER


MAX TOTAL HARDNESS


50°f (500 ppm CaCO<sub>2</sub>) Remark - the treated water can be heated up to 75°C - 80°C. above that temperature the ScaleArmor<sup>™</sup> media loses gradually its effectiveness.

Sediment filtration, anti-scale and anti-corrosion conditioning. Max life-span: 6 months. Maintenance: none.

#### **SPECIFICATIONS**

Selected raw materials, suitable for drinking water. Filter medium: polypropylene. End caps: polyethylene. Treatment material: ScaleArmor<sup>™</sup> certified media





#### **CPP ScaleArmor**<sup>™</sup>

MELT-BLOWN POLYPROPYLENE AND ScaleArmor<sup>™</sup> MEDIA - CARTRIDGES WITH DOUBLE OPEN END (DOE)

PART NUMBER	MODEL	NOMINAL HEIGHT	NOMINAL FILTRATION mcr	MAX FLOW RATE I/h	DIMI A	ENSIONS B	mm C
RA5765508	CPP 10 ScaleArmor <sup>™</sup>	10"	5	1300	250	61	28
RA5767508	CPP 20 ScaleArmor <sup>™</sup>	20"	5	1600	505	61	28



# **CPP BIG ScaleArmor**<sup>™</sup>

MELT-BLOWN POLYPROPYLENE AND ScaleArmor<sup>™</sup> MEDIA - CARTRIDGES WITH DOUBLE OPEN END (DOE)

PART		NOMINAL	NOMINAL	MAX	DIMENSIONS mm		
NUMBER	MODEL	HEIGHT	FILTRATION mcr	FLOW RATE I/h			
RA5765608	CPP 10 BIG ScaleArmor <sup>™</sup>	10"	5	2500	250	112	28
RA5767608	CPP 20 BIG ScaleArmor <sup>™</sup>	20"	5	4000	511	112	28

#### **CONFIGURATIONS:**


- SX standard configuration double open end (DOE).

### **MODELS:**

- CPP ScaleArmor<sup>™</sup> series 10 and 20", OD 2.40" and 4.50", ID 1.10", SX configurations.

**CERTIFICATIONS:** 





improving www.atlasfiltri.com | MADE IN ITALY



Scale Armor<sup>™</sup> media is certified by IAPMO R&T against IAPMO Z601 for material safety requirement.