# <sup>™</sup> P 20 BIG ScaleArmor

OD 4,5" replacement cartridge for ScaleArmor™ ROCK certified system



Plastic container filled with certified ScaleArmor<sup>™</sup> media: an anti-scale and anti-corrosion treatment with proven effectiveness that removes with time old calcareous incrustations and offers a corrosion protection for boilers, pipes, pumps and appliances. ScaleArmor<sup>™</sup> ROCK is the IAPMO Z601 certified system that prevents limescale build-up with 86% effectiveness compared to untreated water.

MAX WORKING TEMPERATURE 45°C (113°F) MIN WORKING TEMPERATURE 4°C (39,2°F)



## MAX TOTAL HARDNESS **50°f (500 ppm CaCO<sub>3</sub>)**

Remark - the treated water can be heated up to 75°C - 80°C, above that temperature the ScaleArmor™ media loses gradually its effectiveness.

Anti-scale and anti-corrosion conditioning.

Max life-span: 24 months. Maintenance: none.

Remark - Use a pre-filter to protect the cartridge.

#### **SPECIFICATIONS**

Selected raw materials, suitable for drinking water.


Endcaps: Polypropylene.

Container: PET.

Flat seal: SEBS with antimicrobial technology

Grid: Polypropylene. Net: polyester.

Treatment material: ScaleArmor™ certified media



### P 20 BIG ScaleArmor™

CONTAINER WITH ScaleArmor™ MEDIA WITH DOUBLE OPEN END (DOE)

PART Number	MODEL	NOMINAL HEIGHT	MAX FLOW RATE I/h	DIMENSIONS mm A B C		
	OD 4,50" x ID 1,10"					
RA5197635	P 20 BIG ScaleArmor™	20"	2270	508	120	28



### REFILL AVAILABLE (1 REFILL = 1 FILLED CARTRIDGE):

PART NUMBER: RA5199698
Use only the original ScaleArmor™ refill to maintain the certified effectiveness.



#### **MODELS:**

- P 20 BIG ScaleArmor™ series 20", OD 4.50", ID 1.10". SX configuration.







