



BIG

10"/20"



Container with

# STRONG BASE ANION EXCHANGE RESIN

for the reduction of




IT'S MADE IN ITALY



4.5" OD container with strong base anion exchange resin for DP BIG housings

Plastic container filled with anti-nitrate selective strong base anion exchange resin, for the reduction of nitrate content in drinking water. The concentration of nitrates in drinking water below 50 mg/l (as NO<sub>3</sub>\*) is strongly recommended by World Health Organization (WHO) guidelines. QA AF BIG cartridges are available in 10" and 20" height.



MAX WORKING TEMPERATURE
45°C (113°F)
MIN WORKING TEMPERATURE
4°C (39,2°F)



COLDWATER

Reduction of nitrates.

Media life-span: see the graph.

Maintenance: none.

Remark - Use a pre-filter to protect the cartridge.

Treatment material: strong base anion exchange resin,

nitrates selective.

 $\begin{array}{l} {\rm Max\ concentration\ NO_3:\ 200\ ppm} \\ {\rm Max\ concentration\ SO_4^2:200\text{-}300\ ppm} \end{array}$ 


#### **CONTAINER TECHNICAL SPECIFICATIONS**

Selected raw materials, suitable for drinking water.


Endcaps: Polypropylene Container: PET

Flat seal: SEBS with antimicrobial technology

Grid: Polypropylene Felt pad: Polyester







# QA AF BIG SX

PART	MODEL	NOMINAL	RECOMMENDED	DIMENSIONS mm		
NUMBER	(OD 4.50" x ID 1.10")	HEIGHT	FLOW RATE I/h		В	
RA5355625	QA AF 10 BIG SX TS	10"	110	250	120	28
RA5357625	QA AF 20 BIG SX TS	20"	200	508	120	28







QAAF BIG cartridges are tested and certified under the most stringent procedures worldwide, in compliance with the sanitary certifications DM25 -Italy- and EAC/Ghostreghistrazia -Russia- (complete cartridge) and ACS -France- (only empty container).

-Russia- (complete cartridge) and ACS -France- (only empty container). Resin is in compliance with EU Regulation No 1935/2004 corresponds to the definition contained in FDA CFR 21 - 173.25.



P 10 BIG SX TS, P 10 BIG SX AB, P 10 BIG SX BW, P 20 BIG SX TS, P 20 BIG SX AB and P 20 BIG SX BW empty containers are certified by IAPMO R&T against NSF/ANSI Standards 42, 61, 372 and CSA B483.1 for material safety and lead free requirements.




### **REFILL AVAILABLE (1 refill = 10" - 2 refills = 20"):**

RA5359625 STRONG BASE ANION EXCHANGE RESIN

# **SPARE PARTS KIT AVAILABLE:**

LB7707175







**ATLAS FILTRI S.r.I.** I Via Pierobon, 32 | 35010 Limena (PD) Italy Tel. +39.049.76.90.55 | Fax +39.049.76.99.94 | **www.atlasfiltri.com**